

SYMBOL(S)	ITEM NO.	USED TO MOUNT	QTY	USED ON		
				MODEL	ASSY. NO.	DATE
				MSA-1	A3398	3/26/65
					A3403	

SYMBOL(S)	ITEM NO.	USED TO MOUNT	QTY	REQ. PER UNIT	REQ. ITEM	PART NO.	DESCRIPTION	SYMBOL
DS6501-6504	1			1	3	WL100-6	WIRE, ELEC, BUSS -SZ 20	
G6514	3				4	TS106-3	LIGHT, IND	
J6516	4				1	TE111-2	TERM., LUG, 3/8D	
M6501-6504	7				1	SW150	SW, ROTARY	
R6552-6555	10				1	SW120	SW, ROTARY	
R6551	11				4	SFB0256SN3	SCR, TAP., THD CTG	
R6556, 6558	12				4	RV4NAYSD505A	RES, VAR-COMP	
R6560, 6562	12				1	RV4NAYSD104A	RES, VAR-COMP	
S6502	13	NP616	4		4	RC20GF105J	RES, FXD, COMP	
S6501	14				12	PX104-1-034	INS SLVG, SZ 20 -BLK	
XDS6501-6504	17	R6551	1		1	NP616	PLATE, IDENT-COML	
					4	MR154	METER, AUDIO LVL	
					7	MP123-1FB	KNOB	
					1	LD1401/MS3562	PNL, FRONT	
					1	JJ034	JACK, TEL	
					1	CN112A105M2	CAP., FXD, MTLZ P	
					2	BS100	SOLDER, TIN ALY	
					4	BI101-47	LAMP, INCAND	
							POSE	
							THE TECHNICAL MATERIEL CORP. MAMARONECK, NY	
							PANEL ASSEMBLY, FRONT	
							3-24-65 ENG COORD	
							6-23-65	
							CHECKED	
							DRAWN	
							TYPE & TEMPER	
							HEAT TREAT. SPEC.	
							MATERIAL	
							FINISH & SPEC. NO.	
							ELEC. DES. APP.	
							MECH. DES. APP.	
							A3403	
							FINAL APPROVAL	

ORIGINAL RELEASE FOR PRODUCTION
 DATE 6/24/65
 SCALE
 UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES AND INCLUDE CHEMICALLY APPLIED OR PLATED FINISHES
 TOLERANCES
 DECIMALS
 .X ± .05
 .XX ± .01
 .XXX ± .005
 FRACTIONS
 ± 1/64
 ANGLES
 ± 0° 30'