



NOTE:  
 INDICATES ITEM 5 ATTACHED TO WIRE AT NAIL POINT.  
 INDICATES WIRE MARKER, ITEM 7

WIRES SHOULD BE PLACED IN CABLE IN NUMERICAL SEQUENCE AS THEY APPEAR IN ITEM COLUMN. SPACE LACING APPROXIMATELY 3/4" APART.

THIS SYMBOL DENOTES END OF INSULATION AND NAIL DRIVING POINT. WIRE MUST BE STRIPPED 3/4" BEYOND THIS POINT AND TINNED 1/2" UNLESS OTHERWISE SPECIFIED.

CA-863

REVISIONS					
SYM	DESCRIPTION	DATE	E.M.N. NO.	DRAFT	CHKD APPD
X1	ADDED ITEM 7	4/8/64		TR	TR
0	ORIGINAL RELEASE FOR PRODUCTION	4-17-64	0	A.M.	@

REQ'D.	ITEM	PART NUMBER	DESCRIPTION	SYMBOL
X	7	LA-101	WIRE MARKERS	
X	6	CD-101-1-MW	CORD, LACING	
8	5	PL-204	CONNECTOR, MIN. FEMALE	
13"	4	RG-174/U	CABLE, COAXIAL	
13"	3	↑ ↑	↑ ↑	
13"	2	↓ ↓	↓ ↓	
13"	1	RG-174/U	CABLE, COAXIAL	

AALTONEN LIST OF MATERIAL

**THE TECHNICAL MATERIEL CORP.**  
 AALTONEN MAMARONECK, NEW YORK

TITLE: WIRING, HARNESS IF TO PROD. DET. CABLE

UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES AND INCLUDE CHEMICALLY APPLIED OR PLATED FINISHES

DECIMALS .X ± .05 .XX ± .01 .XXX ± .005	TOLERANCES	FRACTIONS ± 1/64 ANGLES ± 0° 30'
--	------------	---

DRAWN: WTB.	DATE: 2.28.64	FINAL APPROVAL: [Signature]	DATE:
CHECKED: @	DATE: 4/8/64		
ELECT. DES: [Signature]	DATE: 4/8/64	CA-863	0
MECH. DES: [Signature]	DATE: 4/8/64		

SHEET

1	MSA-1	
Q'TY./UNIT	MODEL USED ON	ASS'Y. NO.
SCALE: 1:1	CODE: A	

THE CONTENTS OF THIS DRAWING ARE THE EXCLUSIVE PROPERTY OF THE TECHNICAL MATERIEL CORP. ITS UNAUTHORIZED USE OR REPRODUCTION IN WHOLE OR IN PART IS STRICTLY FORBIDDEN.

NOTES