

CH-203

FOR SALES USE ONLY NOT FOR MANUFACTURING

TEST CHART GPT-10KL

SPECIAL FOR CANADIAN EXPORT

TEST FREQ. (KCS)	VMO FREQ.	DRIVER BAND	IPA BAND	1st AMP TUNE	IPA GRID TUNE	IPA TUNE	IPA LOAD	IPA LOAD POS	Ip IPA	FINAL BAND	PA TUNE	PA LOAD	OUTPUT LOAD	Ip PA	Isg PA	PA PLATE RF	S/D DB	LOAD CURRENT
2000	2250	2-4	2-2.5							2-3								
2500	2750	2-4	2-2.5							2-3								
2500	2750	2-4	2.5-3							2-3								
3000	3250	2-4	2.5-3							2-3								
3000	3250	2-4	3-4							3-4								
3273	3523	2-4	3-4							3-4								
4000	3750	2-4	3-4							3-4								
4000	3750	4-8	4-6							4-6								
4648	3206	4-8	4-6							4-6								
4840	3410	4-8	4-6							4-6								
5802.5	2357.5	4-8	4-6							4-6								
6000	2250	4-8	4-6							4-6								
6000	2250	4-8	6-8							6-8								
7810	2440	4-8	6-8							6-8								
8000	2250	4-8	6-8							6-8								
8015	2235	8-16	8-12							6-8								
8035	2215	8-16	8-12							8-11								
9075	3175	8-16	8-12							8-11								
10910	3340	8-16	8-12							8-11								
11045	3205	8-16	8-12							8-11								
11605	2645	8-16	8-12							11-15								
11665	2585	8-16	8-12							11-15								
11980	2270	8-16	8-12							11-15								
12000	2250	8-16	12-16							11-15								
14920	3330	8-16	12-16							11-15								
15000	3250	8-16	12-16							15-19								
15620	2630	8-16	12-16							15-19								
15839.5	2410.5	8-16	12-16							15-19								
16000	2250	8-16	12-16							15-19								
16030	2220	16-20	16-20							15-19								
16350	3900	16-20	16-20							15-19								
18828.18	3421.82	16-20	16-20							15-19								
19000	3250	16-20	16-20							15-19								
19000	3250	16-20	16-20							19-24								
19226.4	3023.6	16-20	16-20							19-24								
20000	2250	16-20	16-20							19-24								
20000	2250	20-28	20-28							19-24								
24000	2250	20-28	20-28							19-24								
24000	2250	20-28	20-28							24-28								
28000	2250	20-28	20-28							24-28								
7382.5	2867.5	4-8	6-8															
13540	2710	8-16	12-16															
14535	3815	8-16	12-16															
14805	3445	8-16	12-16															

12.2 AMPS RF REQUIRED

12.2 AMPS RF REQUIRED

10 AMPS RF REQUIRED

12.2 AMPS

TEST CONDITIONS 50 OHM UNBALANCED LOAD

TEST:

- 6.1.1 - Power Output \_\_\_\_\_ 6.8 - Audio bandswitch \_\_\_\_\_
- 6.1.1.2 - Third order distortion \_\_\_\_\_ 6.9 - Spurious radiation \_\_\_\_\_
- 6.1.2 - CW Output \_\_\_\_\_ 6.11 - Hum level \_\_\_\_\_
- 6.7 - Carrier level \_\_\_\_\_

STOCK SIZE		THE TECHNICAL MATERIEL CORP. MAMARONECK, NEW YORK		
MATERIAL		SALES ORDER NUMBER	PROPOSAL NUMBER	QR NUMBER
TYPE & TEMPER HEAT TREAT. & SPEC.		TITLE: TEST CHART GPT-10KL SPECIAL FOR CANADIAN EXPORT		
FINISH & SPEC. NO.		L. Lib. 5/9/61	AM 7/16/69	CH-203
DRAWN BY		DATE	FINAL APPROVAL	NO. OF SH.