

THE CONTENTS OF THIS DRAWING ARE THE EXCLUSIVE PROPERTY OF THE TECHNICAL MATERIEL CORP. ITS UNAUTHORIZED USE OR REPRODUCTION IN WHOLE OR IN PART IS STRICTLY FORBIDDEN.

CH-220

TUBE	TYPE	FUNCTION	SOCKET PIN NUMBERS								
			1	2	3	4	5	6	7	8	9
V4001	6S4	MIXER	INF	3.9K	0.8	Fil.	0	0.8	INF	INF	25K
V4002	6BA6	AMPLIFIER	33K	1.2K	Fil.	0	26K	45K	1.2K		
V4003	6S4	MIXER	INF	3.6K	50K	Fil.	0	50K	INF	INF	25K
V4004	6BA6	AMPLIFIER	55	1.5K	Fil.	0	24K	41K	1.5K		
V4005	6U8	AMPLIFIER	24K	10K	34K	0	Fil.	25K	220	180	10K
V4006	6AB4	OSCILLATOR	14K	0	0	Fil.	INF	470K	0		

CONDITIONS:

ALL MEASUREMENTS TAKEN WITH OHMMETER, SIMPSON TYPE 260 OR EQUIVALENT.

ALL RESISTANCES ARE TO GROUND.

ALL POWER IS TURNED OFF.

K = ONE THOUSAND.

REF: CK-575

SYM	DESCRIPTION	DATE	CH. NO.	DRAFTS	CHECKER	ENG. APP.
UNLESS OTHERWISE SPECIFIED:		SCALE:				
DIMENSIONS ARE IN INCHES		MAXIMUM ALLOWABLE TOLERANCES HAVE BEEN DETERMINED AND ANY DEVIATIONS WILL BE CAUSE FOR REJECTION.				
TOLERANCES ON FRACTIONS $\pm 1/64$ DECIMALS $\pm .005$ ANGLES $\pm 1/2^\circ$		REMOVE ALL BURRS AND SHARP EDGES				

REQ. PER UNIT	MODEL	SECTION	ASS'Y. NO.	DATE
	HNF-1			7-26-62
USED ON				

REQ.	ITEM	PART NO.	DESCRIPTION	SYMBOL
			GELLMAN	
STOCK SIZE			THE TECHNICAL MATERIEL CORP., MAMARONECK, NEW YORK	
MATERIAL			RESISTANCE CHART (MODEL HNF-1)	
TYPE & TEMPER		HEAT TREAT. SPEC.	DRAWN	CHECKED
			R.H.	BP
FINISH & SPEC. NO.			ELEC. DES. APP.	MECH. DES. APP.
				CH-220