



NOTES:
 SHELL MATERIAL - ALUMINUM ALLOY
 SHELL FINISH - CADMIUM PLATE
 INSERT INSULATION - FABRICATED PHENOLIC

CONTACTS:

TOTAL CONTACTS - 12	MIN. CLEARANCE
4 10amp (#1,3,4,7)	1/16
2 15amp (#5,6)	11/64
2 15amp (#2,8)	3/64
4 Coaxials (10amp.)	Grounded

NOTICE TO PERSONS RECEIVING THIS DRAWING
 THE TECHNICAL MATERIEL CORPORATION claims proprietary right in the material disclosed hereon. This drawing is issued in confidence for engineering information only and may not be reproduced or used to manufacture anything shown hereon without permission from THE TECHNICAL MATERIEL CORPORATION to the user. This drawing is loaned for mutual assistance and is subject to recall at any time.
 Property of:
 THE TECHNICAL MATERIEL CORPORATION
 MAMARONECK, NEW YORK

REF- CANNON ELECT. CO. Type DPD-12C4-335-1A

CHANGED FROM	DATE	CH. NO.	DRAFTS	CHECKER	ENG. APP.
Pictorial Clarified	4/23/58	2		J.M.D.	
Shell was Tin Plate-Lacquered	5/28/57	1	16	J.M.D.	
1 11/16 Depth was 1 37/64					
REDRAWN					

REQ. PER UNIT	MODEL	PROJECT NO.	ASS'Y. NO.	DATE
1 Each	FFRD-5,6,7,8		A-325	5-28-57
1 Each	FFRD-1,2,3			5-28-57

REQ. ITEM	PART NO.	DESCRIPTION	SYMBOL
//		THE TECHNICAL MATERIEL CORP. MAMARONECK, NEW YORK	
//		CONNECTOR, PLUG, ELECTRICAL MULTI-COAXIAL	
//		165-28-57	J.M.D. M.P.
TYPE & TEMPER	HEAT TREAT. SPEC.	DRAWN	CHECKED
FINISH & SPEC. NO.	ELEC. DES. APP.	MECH. DES. APP.	

±
 DIM. ±
 FAR DIM. ±

SCALE:
 MAXIMUM ALLOWABLE TOLERANCES HAVE BEEN DETERMINED AND ANY DEVIATIONS WILL BE CAUSE FOR REJECTION.
 REMOVE ALL BURRS AND SHARP EDGES

USED ON

PL-109