

DATE <u>8/7/57</u>	TMC SPECIFICATION NO. S -340 A
SH. <u>1</u> OF <u>1</u>	
COMPILED BY <u>J. De</u>	TITLE: QDP PANEL ASSEMBLY NOMENCLATURES & CABLE ASSY.
APPROVED <u>A. J. J.</u>	JOB

~~OBSOLETE~~

OBSOLETE STANDARD MODELS QDP
MODEL DESCRIPTION

- QDP-1S4(A) QDL to QDL, 4 connections w/switches, w/o plugs.
- QDP-14(B) QDL to QDL, 4 connections, w/o switches, w/8 each PL-136.
- QDP-1S4(B) QDL to QDL, 4 connections, w switches, w/8 each PL-136.
- QDP-24(A) QDL to QDS, 4 connections, w/o switches, w/o plugs.
- QDP-24(B) QDL to QDS, 4 connections, w/4 each PL-136 and 4 each PL-149.
- QDP-38(A) QDS to QDS, 8 connections, w/o switches, w/o plugs.
- QDP-3S8(B) QDS to QDS, 8 connections, w/switches, w/8 each PL-149.

QDP PANEL ASSEMBLY NOMENCLATURES

QDP	2	S	4	A
Basic Titles	Series	Switches (if any)	Number of connections per panel	A-without plugs B-with plugs

Where the letter "S" is included in the panel assembly nomenclature, a set of DPST switches are provided which are actuated by a plunger type contact upon connection of the plug as follows:

- PL-136 QDL straight plug, u/w RG-35 or 164/U.
Equivalent to UG-1020/U.
- PL-141 QDL right angle plug.
Equivalent to UG-1061A/U.
- PL-149 QDS straight plug, u/w RG-8, 10, 11, 12/U.
Equivalent to UG-968/U.

Patching cable assemblies are available in various lengths for use in inter-connecting QDP panels. The cable consists of flexible cable with appropriate connectors on each end. For special applications, such as QDS to UHF, QDL to IC, etc, assemblies can be made upon request.

The basic part number for these cables is CA-323. The part number is followed by an "L" if QDL, or by "S" if QDS, then by a figure indicating the length in feet, i.e., CA-323-S4 is a cable with QDS plugs, four feet in over-all length.

NOTE: Cable Assembly CA-343-X is used only on QDP-2S4
X = Cable length to be supplied by customer.

